(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



| 1851 | 1871 | 1871 | 1871 | 1871 | 1871 | 1871 | 1871 | 1871 | 1871 | 1871 | 1871 | 1871 | 1871 | 1871 | 187

(43) International Publication Date 19 August 2004 (19.08.2004)

PCT

(10) International Publication Number WO 2004/070346 A2

(51) International Patent Classification7:

G01N

(21) International Application Number:

PCT/GB2004/000197

(22) International Filing Date: 20 January 2004 (20.01.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0302434.6

3 February 2003 (03.02.2003) GB

(71) Applicant (for all designated States except US): SENSOR HIGHWAY LIMITED [GB/GB]; 8th Floor, South Quay Plaza, 183 Marsh Wall, London E14 9SH (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): HARTOG, Arthur, H. [CA/GB]; 31 Butterfield Road, Southampton SO16 7EG (GB).

(74) Agent: KANAK, Wayne, I.; Gamma House, Enterprise Road, Chilworth Science Park, Southampton SO16 7NS (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

 without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



8

(54) Title: INTERFEROMETRIC METHOD AND APPARATUS FOR MEASURING PHYSICAL PARAMETERS

(57) Abstract: A method of measuring a selected physical parameter at a location within a region of interest comprises the steps of: launching optical pulses at a plurality of reselected interrogation wavelengths into an optical fibber (1) deployed along the region of interest, reflectors $(2_0.2_1,2_n)$ being arrayed along the optical fibber (1) to form an array (9) of sensor elements, the optical path length between the said reflectors (2) being dependent upon the selected parameter; detecting the returned optical interference signal for each of the reselected wavelengths; and determining from the optical interference signal the absolute optical path length (L) between two reflectors (2) at the said location, and from the optical path length (L) so determined the value of the selected parameter at the said location; wherein the step of determining the absolute optical path length (L) comprises carrying out a process in which the phase difference between the interference signals for a pair of the reselected wavelengths is estimated using an estimated value for the optical path length (L), the estimated phase difference is used to estimate the phase at each of those wavelengths, and the phase thus obtained is used to revise the estimated value for the optical path length (L), the process being repeated for some or all remaining wavelength pairs in sequence, on the basis of the optical path length (L) estimated for the immediately preceding pair in the sequence, thereby to progressively revise the optical path length (L) until it is know to a desired level of accuracy.